

Printing date 27.06.2011

Revision: 27.06.2011

1 Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- · Trade name: UHU extra All Purpose Adhesive
- \cdot Relevant identified uses of the substance or mixture and uses advised against
- \cdot Application of the substance / the preparation Adhesives
- \cdot Details of the supplier of the safety data sheet
- Manufacturer/Supplier: UHU GmbH & Co.KG Herrmannstraße 7 D-77815 Bühl (Baden) Tel.:0049-(0)7223-284-0 email: info@uhu.boltongroup.de

Fax: 0049-(0)7223-284-245

• Further information obtainable from: CRD

• Emergency telephone number: 0049-(0)7223284-363/-370

2 Hazards identification

Classification of the substance or mixture
 Classification according to Regulation (EC) No 1272/2008

GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC

F; Highly flammable

R11: Highly flammable.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· Label elements

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

The R and S phrases may be omitted if packaging contains no more than 0.125 litre.

• Code letter and hazard designation of product: F Highly flammable

• **Risk phrases:** 11 Highly flammable.

· Safety phrases:

- 7/9 Keep container tightly closed and in a well-ventilated place.
- 16 Keep away from sources of ignition No smoking.
- 23 Do not breathe fumes/aerosol.
- 51 Use only in well-ventilated areas.

(Contd. on page 2)

GB -



Printing date 27.06.2011

Revision: 27.06.2011

Trade name: UHU extra All Purpose Adhesive

(Contd. of page 1)

- Special labelling of certain preparations:
- After article 10 no. 4 of DIRECTIVE 1999/45/EC it shall not be necessary to indicate the R phrases or the S phrases, if the contents of the package do not exceed 125 ml.

· Other hazards

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- Chemical characterization: Mixtures
- · Description: Adhesive

· Dangerous components:		
	methyl acetate	25-50%
EINECS: 201-185-2	🗙 Xi R36; 🎽 F R11	
	R66-67	
	🚸 Flam. Liq. 2, H225; 🚸 Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 64-17-5	ethanol	25-50%
EINECS: 200-578-6	▶ F R11	
	🐼 Flam. Liq. 2, H225	
· Additional informati	on: For the wording of the listed risk phrases refer to section 16.	

4 First aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Do not induce vomiting; call for medical help immediately.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Pick up mechanically.
- **Reference to other sections** See Section 7 for information on safe handling.

(Contd. on page 3)



Printing date 27.06.2011

Revision: 27.06.2011

(Contd. of page 2)

Trade name: UHU extra All Purpose Adhesive

See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- Information about fire and explosion protection:
- Keep ignition sources away Do not smoke.
- Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace:
- 79-20-9 methyl acetate
- WEL () Short-term value: 770 mg/m³, 250 ppm
 - Long-term value: 616 mg/m³, 200 ppm

64-17-5 ethanol

- WEL () Long-term value: 1920 mg/m³, 1000 ppm
- Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:
- The usual precautionary measures are to be adhered to when handling chemicals.

Avoid direct contact with the chemical/ the product/ the preparation by organizational measures.

- · Respiratory protection: Not required.
- Protection of hands:
- Solvent resistant gloves
- Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- · Penetration time of glove material
- The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- Eye protection: Not required.

(Contd. on page 4)



Printing date 27.06.2011

Revision: 27.06.2011

Trade name: UHU extra All Purpose Adhesive

(Contd. of page 3)

Information on basic physics	al and chemical properties
General Information Appearance:	
Form:	Fluid
Colour:	Colourless
Odour:	Characteristic
Change in condition Melting point/Melting rang Boiling point/Boiling rang	
Flash point:	-10°C
Ignition temperature:	425°C
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapou mixtures are possible.
Explosion limits:	
Lower:	3.1 Vol %
Upper:	16.0 Vol %
Vapour pressure at 20°C:	220 hPa
Density at 20°C:	0.95 g/cm ³
Solubility in / Miscibility with water:	h Partly miscible.
Viscosity: Dynamic at 20°C:	90000 mPas
Solvent content:	
Organic solvents:	68.8 %
Water:	0.4 %
VOC (EC)	68.85 %
Solids content:	30.8 %
Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

· LD/LC50 values relevant for classification:

79-20-9 methyl acetate

Oral LD50 3705 mg/kg (rabbit)

(Contd. on page 5)

GB



Printing date 27.06.2011

Revision: 27.06.2011

(Contd. of page 4)

Trade name: UHU extra All Purpose Adhesive

64-17-5 ethanol

Oral	LD50	7060 mg/kg (rat)
Inhalative	LC50/4 h	20000 mg/l (rat)

· Primary irritant effect:

• on the skin: No irritant effect.

• on the eye: No irritating effect.

• Sensitization: No sensitizing effects known.

12 Ecological information

- · Toxicity
- · Acquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow product to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be made according to official regulations.

· European waste catalogue

08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

· UN-Number		
· ADR, IMDG, IATA	UN1133	
· UN proper shipping name		
ADR	1133 KLEBSTOFFE, Sondervorschrift 640H	
· IMDG, IATA	ADHESIVES	
• Transport hazard class(es)		
ADR		
· Class	3 Flammable liquids.	



Printing date 27.06.2011

Revision: 27.06.2011

Trade name: UHU extra All Purpose Adhesive

	(Contd. of page
· Label	3
· IMDG, IATA	
· Class	3 Flammable liquids.
· Label	3
· Packing group	
· ADR, IMDG, IATA	III
· Environmental hazards:	
• Marine pollutant:	No
\cdot Special precautions for user	Warning: Flammable liquids.
· Danger code (Kemler):	33
· EMS Number:	F-E,S-D
• Transport in bulk according to Annex	II of
MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
\cdot Limited quantities (LQ)	5L
· Transport category	3
• Tunnel restriction code	D/E
· UN "Model Regulation":	UN1133, ADHESIVES, special provision 640H, 3, III

15 Regulatory information

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
R11 Highly flammable.
R36 Irritating to eyes.
R66 Repeated exposure may cause skin dryness or cracking.
R67 Vapours may cause drowsiness and dizziness.

- Department issuing MSDS: CRD
 Contact: Frau A. Liar, Herr Dr. C. Hanf
 Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- Carriage of Dangerous Goods by Road) RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- ICAO: International Civil Aviation Organization

(Contd. on page 7)

GB



Printing date 27.06.2011

Revision: 27.06.2011

Trade name: UHU extra All Purpose Adhesive

GHS: Globally Harmonized System of Classification and Labelling of Chemicals VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent (Contd. of page 6)

GB —